



8755 W. Higgins Road
Suite 500
Chicago, Illinois USA 60631

Oct 11th, 2016

RE: PCN # ESW490_28 TO-220(Isolated & non-isolated) TO-263(D2Pak) & TO218(Isolated & non-isolated) Package Solder Paste Property Change

To our valued customers,

Littelfuse would like to notify you of a newly approved solder paste type Pb92.5Sn5Ag2.5 for all TO-220 Isolated/non-Isolated , TO-263(D2PAK), and TO218(Isolated & non-isolated) Thyristor products. The new solder paste type is fully approved internally. It will enable further improvement in quality enhancement, and process control.

Qualification efforts have been completed. Please see the attached documentation for change detail and affected part numbers.

All affected products have been fully qualified in accordance with established performance and reliability criteria. The attached pages summarize the qualification results. Full qualification data and/or samples will be available upon request.

Form, fit, function changes: None

Part number changes: None

Effective date: Jan 11th, 2017

Replacement products: N/A

Last time buy: N/A

This notification is for your information and acknowledgement. If you have any other questions or concerns, please contact your local sales team or Zhiwei Wang, Assistant Product Manager.

We value your business and look forward to assisting you whenever possible.

Best Regards,

Zhiwei Wang
Semiconductor Business Unit, Wuxi, China
+86 510 85277701 - 7927
zwang@littelfuse.com



800 E. Northwest Highway Des Plaines, IL 60016

Product/Process Change Notice (PCN)

PCN#: ESW490-28 **Date:** Oct 11, 2016

Product Identification:

All TO-220(Isolated & non-isolated) TO-263(D2PAK) & TO218(Isolated & non-isolated)

Implementation Date for Change:

Jan 11, 2017

Contact Information

Name: Zhiwei Wang

Title: Assistant Product Manager

Phone #: +86 510 85277701 - 7927

Fax#: N/A

E-mail: zwang@littelfuse.com

Category of Change:

- Assembly Process
- Data Sheet
- Technology
- Discontinuance/Obsolescence
- Equipment
- Manufacturing Site
- Raw Material
- Testing
- Fabrication Process
- Other: _____

Description of Change:

Approve a new solder paste type Pb92.5Sn5Ag2.5 for all TO-220 Isolated/non-Isolated , TO-263(D2PAK) , and TO218(Isolated & non-isolated) Thyristor products

The affected products have been fully qualified in accordance with all established criteria for performance and reliability

All relevant detail is included in the supplemental pages..

Important Dates:

Qualification Samples Available: Oct 11, 2016, sample available upon request

Last Time Buy:

Final Qualification Data Available: Oct 11,2016

Date of Final Product Shipment:

Method of Distinguishing Changed Product

- Product Mark,
- Date Code, Start from 7BXXX
- Other,

Demonstrated or Anticipated Impact on Form, Fit, Function or Reliability:

None

LF Qualification Plan/Results:

Attached..... full detail available upon request

Customer Acknowledgement of Receipt: Littelfuse requests you acknowledge receipt of this PCN. In your acknowledgement, you can grant approval or request additional information. Littelfuse will assume the change is acceptable if no acknowledgement is received within 30 days of this notice. Lack of any additional response within 90 days of PCN issuance further constitutes acceptance of the change.



PCN Report

ETR # 84716,

84718,84596,84490,84717,84719,84622,84491,84748,84750,84752,84754,84720,
86002,86007,85999,86000

Prepared By : Maggie Xu, Senior Product Engineer
Date : Oct/11/2016
Device : TO220/TO263/TO218 Series Package Product
Revision : A

1.0 Objective:

The purpose of this project is to qualify the use of Pb92.5Ag2.5Sn5 as a new solder paste material for Thyristor TO220 (Isolated and Non-Isolated), TO263 (D2Pak) and TO218 (Isolated and Non-Isolated) Products.

Package	Original Solder paste	New Solder Paste
TO220	Pb90Sn10	Pb92.5Ag2.5Sn5
TO263	Pb90Sn10	Pb92.5Ag2.5Sn5
TO218	Pb90Sn10	Pb92.5Ag2.5Sn5

2.0 Applicable Devices:

Thyristor TO220 (Isolated and Non-Isolated), TO263 (D2Pak) and TO218 (Isolated and Non-Isolated) Product Series

3.0 Packing Method:

There will be no changes in the packing method.

4.0 Physical Differences/Changes:

There is no change in mechanical specification and package outline dimension (POD).

5.0 Reliability Test Results Summary:

Test Category	Description	Sample P/N	Sample Qty	Littelfuse test Ref#	Contents/Conditions	Result Summary
Parametric Test	Electrical Parameters	S4008LS2TP	271	84716	IGT/VGT/IH>IDRM/IRRM	Meet datasheet spec
		Q4010N5RP	271	84718		
		Q6016NH6RP	261	84596		
		Q8025LH5TP	271	84490		
		Q6040K7TP	271	86002		

		S8065KTP	271	86007		
		Q6025K6TP	271	86007		
	High Temperature leakage test	S4008LS2TP	5	84717	AC600Vpeak, 110°C	
		Q4010N5RP	5	84719	AC600Vpeak, 125°C	
		Q6016NH6RP	5	84622		
		Q8025LH5TP	5	84491		
		Q6040K7TP	5	86000		
		S8065KTP	5	86000		
		Q6025K6TP	5	86000		
	ITSM	S4008LS2TP	5	84748	Single half cycle; f = 50Hz; T _J (initial) = 25°C	
		Q4010N5RP	5	84750		
		Q6016NH6RP	5	84752		
		Q8025LH5TP	5	84754		
		Q6040K7TP	5	86000		
		S8065KTP	5	86000		
		Q6025K6TP	5	86000		
	Thermal Resistance	S4008LS2TP	3	84717		
		Q4010N5RP	3	84719		
		Q6016NH6RP	3	84622		
		Q8025LH5TP	3	84491		
Q6040K7TP		3	85999			
Q6025K6TP		3	85999			
Reliability Test	AC Blocking	S4008LS2TP	77	84716	Ta:110°C, 1,008hr, Reverse biased at 400Vpeak AC	no failure at 1,008hr read point
		Q4010N5RP		84718	Ta:125°C, 1,008hr, Reverse biased at 400Vpeak AC	
		Q6016NH6RP	77	84596	Ta:125°C, 1,008hr, Reverse biased at 600Vpeak AC	
		Q6025K6TP	77	86007		
		Q6040K7TP	77	86002		
		S8065KTP	77	86007		
		Q8025LH5TP	77	84490		
	High Humidity High Temp. Reverse Bias (H3TRB)	S4008LS2TP	77	84716	Ta: 85°C, RH: 85%, 1,008hr, Reverse biased at 160V _{DC}	no failure at 1,008 hr read point
		Q4010N5RP		84718		
		Q6016NH6RP	77	84596		
		Q6040K7TP	77	84490		
		Q6025K6TP	77	86002		
		Q8025LH5TP	77	86007	Ta: 85°C, RH: 85%, 1,008hr, Reverse biased at	
		S8065KTP	77	86007		

					320V _{DC}		
Temperature Cycling (TC)	S4008LS2TP	77	84716	-40°C & 150°C (air to air), Dwell time 15mins, 100 cycles	0 failure at 100cycle read point		
	Q4010N5RP	77	84718				
	Q6016NH6RP	77	84596				
	Q8025LH5TP	77	84490				
	Q6040K7TP	77	86002				
	S8065KTP	77	86007				
	Q6025K6TP	77	86007				
Solderability	S4008LS2TP	10	84716	ANSI/J-STD-002, category 3, Test A	no failure after solderability		
	Q4010N5RP	10	84718				
	Q8025LH5TP	10	84490				
	Q6040K7TP	10	86002				
	S8065KTP	10	86007				
	Q6025K6TP	10	86007				
Resistance to Solder Heat (RSH)	S4008LS2TP	30	84716	260°C, 10 seconds	0% failure after RSH		
	Q4010N5RP	30	84718				
	Q6016NH6RP	30	84596				
	Q8025LH5TP	30	84490				
	Q6040K7TP	30	86002				
	S8065KTP	30	86007				
	Q6025K6TP	30	86007				

6.0 Electrical Characteristic Summary:

There is no change in electrical characteristics. Characterization data is available upon request.

7.0 Changed Part Identification:

NA

8.0 Recommendations & Conclusions:

Based on the test results, it is determined that Pb92.5Ag2.5Sn5 is qualified and certified for Thyristor TO220 (Isolated and Non-Isolated), TO263 (D2Pak) and TO218 (Isolated and Non-Isolated) Product Series.

9.0 Approvals:

Maggie Xu
Thyristor Product Engineer
Littelfuse, WUXI

Zhiwei Wang
Product Engineer Manager
Littelfuse, WUXI